

## Material Safety Data Sheet

---

### 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY/UNDERTAKING

**Material Name** : Shell Unleaded E10  
**Recommended Uses** : Fuel for spark ignition engines designed to run on unleaded fuel.

**Other names** : GASOLINE  
**Product Code** : 002D1811

**Manufacturer/Supplier** : **The Shell Company of Australia Limited**  
(ABN 46 004 610 459)  
8 Redfern Road  
Hawthorn East  
Victoria 3123  
Australia

**Telephone** : +61 (0)3 9666 5444  
**Fax** : +61 (0)3 8823 4800

**Emergency Telephone Number** : 1800 651 818 (within Australia only) +61 3 9663 2130 (International)

---

### 2. HAZARDS IDENTIFICATION

HAZARDOUS SUBSTANCE. DANGEROUS GOODS.  
Classified as hazardous according to the criteria of NOHSC, and as Dangerous Goods according to the Australian Dangerous Goods Code.

**Symbol(s)** : F+ Extremely flammable.  
T Toxic.  
N Dangerous for the environment.

**R-phrases(s)** : R45 May cause cancer.  
R46 May cause heritable genetic damage.  
R63 Possible risk of harm to the unborn child.  
R65 Harmful: may cause lung damage if swallowed.  
R12 Extremely flammable.  
R67 Vapours may cause drowsiness and dizziness.  
R38 Irritating to skin.  
R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**S-phrase(s)** : S2 Keep out of the reach of children.  
S29 Do not empty into drains.  
S45 In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).  
S53 Avoid exposure. Obtain special instructions before use.  
S61 Avoid release to the environment. Refer to special instructions/Safety data sheets.  
S62 If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

**Health Hazards** : Vapours may cause drowsiness and dizziness. Slightly irritating to respiratory system. Irritating to skin. Moderately irritating to eyes. Harmful: may cause lung damage if swallowed. Possibility of organ or organ system damage from

## Material Safety Data Sheet

	<p>prolonged exposure; see Chapter 11 for details. Target organ(s): Blood-forming organs. Peripheral nervous system. May cause heritable genetic damage. Possible risk of harm to the unborn child. A component or components of this material may cause cancer. This product contains benzene which may cause leukaemia (AML acute myelogenous leukaemia).</p>
<b>Signs and Symptoms</b>	<p>: Skin irritation signs and symptoms may include a burning sensation, redness, swelling, and/or blisters. If material enters lungs, signs and symptoms may include coughing, choking, wheezing, difficulty in breathing, chest congestion, shortness of breath, and/or fever. The onset of respiratory symptoms may be delayed for several hours after exposure. Breathing of high vapour concentrations may cause central nervous system (CNS) depression resulting in dizziness, light-headedness, headache, nausea and loss of coordination. Continued inhalation may result in unconsciousness and death. Damage to blood-forming organs may be evidenced by: a) fatigue and anaemia (RBC), b) decreased resistance to infection, and/or excessive bruising and bleeding (platelet effect). Peripheral nerve damage may be evidenced by impairment of motor function (incoordination, unsteady walk, or muscle weakness in the extremities, and/or loss of sensation in the arms and legs). Eye irritation signs and symptoms may include a burning sensation and a temporary redness of the eye. Auditory system effects may include temporary hearing loss and/or ringing in the ears.</p>
<b>Safety Hazards</b>	<p>: Extremely flammable. Electrostatic charges may be generated during handling. Electrostatic discharge may cause fire. Liquid evaporates quickly and can ignite leading to a flash fire, or an explosion in a confined space.</p>
<b>Environmental Hazards</b>	<p>: Toxic to aquatic organisms. May cause long-term adverse effects in the environment. Unlike other gasoline components, ethanol is miscible with water.</p>
<b>Additional Information</b>	<p>: This product is intended for use in closed systems only.</p>
<b>SUSDP Schedule</b>	<p>: Not scheduled. When packed in containers having capacity of greater than 20 litres.</p>
<b>SUSDP Schedule</b>	<p>S5. When packed in containers having capacity of less than 20 litres.</p>

---

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

<b>Preparation description</b>	<p>: Complex mixture of hydrocarbons consisting of paraffins, cycloparaffins, aromatic and olefinic hydrocarbons (including benzene at 1.0%v/v maximum), with carbon numbers predominantly in the C4 to C12 range. Contains oxygenated hydrocarbons, including ethanol or other alcohols. May also contain several additives at &lt;0.1% v/v each.</p>
--------------------------------	--

#### Hazardous Components

**Material Safety Data Sheet**

Chemical Identity	CAS	EINECS	Symbol(s)	R-phrases(s)	Conc.
Gasoline, low boiling point naphtha	86290-81-5	289-220-8	F+, Xi, T, Xn, N	R12; R38; R45; R46; R63; R65; R67; R51/53	90.00 - 100.00 %
Ethanol	64-17-5	200-578-6	F	R11	0.00 - 10.00 %

**Additional Information** : Contains Benzene, CAS # 71-43-2. Contains Toluene, CAS # 108-88-3. Contains Ethylbenzene, CAS # 100-41-4. Contains n-Hexane, CAS # 110-54-3. Contains Xylene (Mixed Isomers), CAS # 1330-20-7. Contains Naphthalene, CAS # 91-20-3. Contains Cyclo-hexane, CAS# 110-82-7. Contains Tri-methyl-benzene (all isomers), CAS# 25551-13-7. The amount of oxygenated components is limited at 2.7 % m/m calculated as oxygen. Dyes and markers can be used to indicate tax status and prevent fraud. Refer to chapter 16 for full text of EC R-phrases.

**4. FIRST AID MEASURES**

**Inhalation** : Remove to fresh air. If rapid recovery does not occur, transport to nearest medical facility for additional treatment.

**Skin Contact** : Remove contaminated clothing. Immediately flush skin with large amounts of water for at least 15 minutes, and follow by washing with soap and water if available. If redness, swelling, pain and/or blisters occur, transport to the nearest medical facility for additional treatment.

**Eye Contact** : Flush eyes with water while holding eyelids open. Rest eyes for 30 minutes. If redness, burning, blurred vision, or swelling persist, transport to the nearest medical facility for additional treatment.

**Ingestion** : If swallowed, do not induce vomiting; transport to nearest medical facility for additional treatment. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. If any of the following delayed signs and symptoms appear within the next 6 hours, transport to the nearest medical facility: fever greater than 101 °F (37 °C), shortness of breath, chest congestion or continued coughing or wheezing.

**Advice to Physician** : Treat symptomatically. Persons on disulfiram (Antabuse®) therapy should be aware that the ethyl alcohol in this product is hazardous to them just as is alcohol from any source. Disulfiram reactions (vomiting, headache and even collapse) may follow ingestion of small amounts of alcohol and have also been described from skin contact.

**5. FIRE FIGHTING MEASURES**

Clear fire area of all non-emergency personnel.

**Specific Hazards** : Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. The vapour is heavier than air, spreads along the

## Material Safety Data Sheet

	ground and distant ignition is possible. Will float and can be reignited on surface water.
<b>Suitable Extinguishing Media</b>	: Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.
<b>Unsuitable Extinguishing Media</b>	: Do not use water in a jet.
<b>Protective Equipment for Firefighters</b>	: Proper protective equipment including breathing apparatus must be worn when approaching a fire in a confined space.
<b>Additional Advice</b>	: Keep adjacent containers cool by spraying with water. If possible remove containers from the danger zone. If the fire cannot be extinguished the only course of action is to evacuate immediately. Contain residual material at affected sites to prevent material from entering drains (sewers), ditches, and waterways.

---

### 6. ACCIDENTAL RELEASE MEASURES

Avoid contact with spilled or released material. Immediately remove all contaminated clothing. For guidance on selection of personal protective equipment see Chapter 8 of this Material Safety Data Sheet. For guidance on disposal of spilled material see Chapter 13 of this Material Safety Data Sheet. Observe all relevant local and international regulations. Avoid contact with skin, eyes and clothing. Evacuate the area of all non-essential personnel. Ventilate contaminated area thoroughly. If contamination of sites occurs remediation may require specialist advice. Ensure electrical continuity by bonding and grounding (earthing) all equipment. Take precautionary measures against static discharges.

<b>Protective measures</b>	: Vapour can travel for considerable distances both above and below the ground surface. Underground services (drains, pipelines, cable ducts) can provide preferential flow paths. Do not breathe fumes, vapour. Take measures to minimise the effects on groundwater. Contain residual material at affected sites to prevent material from entering drains (sewers), ditches, and waterways. Shut off leaks, if possible without personal risks. Remove all possible sources of ignition in the surrounding area. Use appropriate containment (of product and fire fighting water) to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers. Attempt to disperse the vapour or to direct its flow to a safe location for example by using fog sprays. Take precautionary measures against static discharge. Ensure electrical continuity by bonding and grounding (earthing) all equipment.
<b>Clean Up Methods</b>	: For large liquid spills (> 1 drum), transfer by mechanical means such as vacuum truck to a salvage tank for recovery or safe disposal. Do not flush away residues with water. Retain as contaminated waste. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely. For small liquid spills (< 1 drum), transfer by mechanical means to a labelled, sealable container for product recovery or safe disposal. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely.

## Material Safety Data Sheet

**Additional Advice** : Notify authorities if any exposure to the general public or the environment occurs or is likely to occur. Local authorities should be advised if significant spillages cannot be contained. Maritime spillages should be dealt with using a Shipboard Oil Pollution Emergency Plan (SOPEP), as required by MARPOL Annex 1 Regulation 26.

---

### 7. HANDLING AND STORAGE

**General Precautions** : Avoid breathing vapours or contact with material. Only use in well ventilated areas. Wash thoroughly after handling. For guidance on selection of personal protective equipment see Chapter 8 of this Material Safety Data Sheet. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material. Air-dry contaminated clothing in a well-ventilated area before laundering. Properly dispose of any contaminated rags or cleaning materials in order to prevent fires. Prevent spillages. Turn off all battery operated portable electronic devices (examples include: cellular phones, pagers and CD players) before operating gasoline pump. Do not use as a cleaning solvent or other non-motor fuel uses. Contaminated leather articles including shoes cannot be decontaminated and should be destroyed to prevent reuse. For comprehensive advice on handling, product transfer, storage and tank cleaning refer to the product supplier.

Vehicle fueling and vehicle workshop areas - Avoid inhalation of vapours and contact with skin, when filling or emptying a vehicle.

**Handling** : When using do not eat or drink. Extinguish any naked flames. Do not smoke. Remove ignition sources. Avoid sparks. Never siphon by mouth. The vapour is heavier than air, spreads along the ground and distant ignition is possible. Avoid exposure.

**Storage** : Drum and small container storage: Keep containers closed when not in use. Drums should be stacked to a maximum of 3 high. Packaged product must be kept tightly closed and stored in a diked (bunded) well-ventilated area, away from, ignition sources and other sources of heat. Use properly labelled and closeable containers. Take suitable precautions when opening sealed containers, as pressure can build up during storage. Tank storage: Tanks must be specifically designed for use with this product. Bulk storage tanks should be diked (bunded). Locate tanks away from heat and other sources of ignition. Cleaning, inspection and maintenance of storage tanks is a specialist operation, which requires the implementation of strict procedures and precautions.

**Product Transfer** : Electrostatic charges may be generated during pumping. Electrostatic discharge may cause fire. Ensure electrical continuity by bonding and grounding (earthing) all equipment. Restrict line velocity during pumping in order to avoid generation of electrostatic discharge ( $\leq 1$  m/sec until fill pipe submerged to twice its diameter, then  $\leq 7$  m/sec). Avoid splash filling. Do NOT use compressed air for filling,

## Material Safety Data Sheet

- discharging, or handling operations. Wait 2 minutes after tank filling (for tanks such as those on road tanker vehicles) before opening hatches or manholes. Wait 30 minutes after tank filling (for large storage tanks) before opening hatches or manholes.
- Recommended Materials** : For containers, or container linings use mild steel, stainless steel. Aluminium may also be used for applications where it does not present an unnecessary fire hazard. Examples of suitable materials are: high density polyethylene (HDPE), polypropylene (PP), and Viton (FKM), which have been specifically tested for compatibility with this product. For container linings, use amine-adduct cured epoxy paint. For seals and gaskets use: graphite, PTFE, Viton A, Viton B.
- Unsuitable Materials** : Some synthetic materials may be unsuitable for containers or container linings depending on the material specification and intended use. Examples of materials to avoid are: natural rubber (NR), nitrile rubber (NBR), ethylene propylene rubber (EPDM), polymethyl methacrylate (PMMA), polystyrene, polyvinyl chloride (PVC), polyisobutylene.; However, some may be suitable for glove materials.
- Container Advice** : Containers, even those that have been emptied, can contain explosive vapours. Do not cut, drill, grind, weld or perform similar operations on or near containers. Gasoline containers must not be used for storage of other products.
- Additional Information** : Ensure that all local regulations regarding handling and storage facilities are followed.

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Occupational Exposure Limits

Naphthalene	AU OEL	TWA	10 ppm	52 mg/m <sup>3</sup>	
	AU OEL	STEL	15 ppm	79 mg/m <sup>3</sup>	
Cyclohexane	AU OEL	TWA	100 ppm	350 mg/m <sup>3</sup>	
	AU OEL	STEL	300 ppm	1,050 mg/m <sup>3</sup>	
Xylene	AU OEL	TWA	80 ppm	350 mg/m <sup>3</sup>	
	AU OEL	STEL	150 ppm	655 mg/m <sup>3</sup>	
Toluene	AU OEL	TWA	50 ppm	191 mg/m <sup>3</sup>	
	AU OEL	STEL	150 ppm	574 mg/m <sup>3</sup>	
	AU OEL	SKIN_DES			Can be absorbed through the skin.
Benzene	AU OEL	TWA	1 ppm	3.2 mg/m <sup>3</sup>	
	SHELL IS	TWA	0.5 ppm	1.6 mg/m <sup>3</sup>	
	SHELL IS	STEL	2.5 ppm	8 mg/m <sup>3</sup>	
n-Hexane	AU OEL	TWA	20 ppm	72 mg/m <sup>3</sup>	
Ethylbenzene	AU OEL	TWA	100 ppm	434 mg/m <sup>3</sup>	
	AU OEL	STEL	125 ppm	543 mg/m <sup>3</sup>	
	AU OEL	TWA	25 ppm	123 mg/m <sup>3</sup>	
Trimethylbenzene, all isomers					

## Material Safety Data Sheet

Ethanol	AU OEL	TWA	1,000 ppm	1,880 mg/m3	
---------	--------	-----	-----------	-------------	--

**Additional Information** : Skin notation means that significant exposure can also occur by absorption of liquid through the skin and of vapour through the eyes or mucous membranes.  
SHELL IS is the Shell Internal Standard.

Material	Source	Hazard Designation
Benzene	AU OEL	Confirmed human carcinogen.

**Exposure Controls** : The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances.  
Appropriate measures include: Use sealed systems as far as possible. Adequate explosion-proof ventilation to control airborne concentrations below the exposure guidelines/limits. Local exhaust ventilation is recommended. Eye washes and showers for emergency use.

**Personal Protective Equipment** : Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.  
AS/NZS 1337: Eye protectors for industrial applications.  
AS/NZS 2161: Occupational protective gloves - Selection, use and maintenance. AS/NZS 1715: Selection, use and maintenance of respiratory protective devices. AS/NZS 1716: Respiratory protective devices.

**Respiratory Protection** : If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter. Where air-filtering respirators are unsuitable (e.g. airborne concentrations are high, risk of oxygen deficiency, confined space) use appropriate positive pressure breathing apparatus. All respiratory protection equipment and use must be in accordance with local regulations.

**Hand Protection** : Personal hygiene is a key element of effective hand care.  
Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, glove thickness, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced.  
Select gloves tested to a relevant standard (e.g. Europe EN374, US F739). When prolonged or frequent repeated contact occurs, Nitrile gloves may be suitable. (Breakthrough time of > 240 minutes.) For incidental contact/splash protection Neoprene, PVC gloves may be suitable.

**Eye Protection** : Chemical splash goggles (chemical monogoggles).  
Approved to EU Standard EN166.

**Protective Clothing** : Chemical resistant gloves/gauntlets, boots, and apron (where risk of splashing).

**Monitoring Methods** : Monitoring of the concentration of substances in the breathing

## Material Safety Data Sheet

	zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.
<b>Environmental Exposure Controls</b>	: Local guidelines on emission limits for volatile substances must be observed for the discharge of exhaust air containing vapour.

---

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: Purple. Liquid.
Odour	: Hydrocarbon
pH	: Data not available
Initial Boiling Point and Boiling Range	: 25 - 210 °C / 77 - 410 °F
Freezing/melting point	: Data not available
Flash point	: < -40 °C / -40 °F
Lower / upper Flammability or Explosion limits	: 1 - 8 %(V)
Auto-ignition temperature	: > 250 °C / 482 °F
Vapour pressure	: 690 - 890 hPa at 37.8 °C / 100.0 °F
Specific gravity	: Data not available
Density	: Typical 0.73 g/cm <sup>3</sup> at 15 °C / 59 °F
Solubility in other solvents	: Data not available
n-octanol/water partition coefficient (log Pow)	: 2 - 6
Kinematic viscosity	: 0.5 - 0.75 mm <sup>2</sup> /s at 40 °C / 104 °F
Vapour density (air=1)	: Data not available

---

### 10. STABILITY AND REACTIVITY

<b>Stability</b>	: Stable under normal conditions of use.
<b>Conditions to Avoid</b>	: Avoid heat, sparks, open flames and other ignition sources.
<b>Materials to Avoid</b>	: Strong oxidising agents.
<b>Hazardous Decomposition Products</b>	: Hazardous decomposition products are not expected to form during normal storage. Thermal decomposition is highly dependent on conditions. A complex mixture of airborne solids, liquids and gases, including carbon monoxide, carbon dioxide and other organic compounds will be evolved when this material undergoes combustion or thermal or oxidative degradation.

---

### 11. TOXICOLOGICAL INFORMATION

<b>Basis for Assessment</b>	: Information given is based on product data, a knowledge of the components and the toxicology of similar products.
<b>Acute Oral Toxicity</b>	: Low toxicity: LD <sub>50</sub> >2000 mg/kg, Rat Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.
<b>Acute Dermal Toxicity</b>	: Low toxicity: LD <sub>50</sub> >2000 mg/kg, Rabbit
<b>Acute Inhalation Toxicity</b>	: Low toxicity: LC <sub>50</sub> >5 mg/l / 4 h, Rat High concentrations may cause central nervous system depression resulting in headaches, dizziness and nausea; continued inhalation may result in unconsciousness and/or

**Material Safety Data Sheet**

	death.
<b>Skin Irritation</b>	: Irritating to skin.
<b>Eye Irritation</b>	: Moderately irritating to eyes (but insufficient to classify).
<b>Respiratory Irritation</b>	: Based on human experience, breathing of vapours or mists may cause a temporary burning sensation to nose, throat and lungs.
<b>Sensitisation</b>	: Not a skin sensitiser.
<b>Repeated Dose Toxicity</b>	: Kidney: caused kidney effects in male rats which are not considered relevant to humans Blood-forming organs: repeated exposure affects the bone marrow. (Benzene) Peripheral nervous system: repeated exposure causes peripheral neuropathy in animals. (n-Hexane)
<b>Mutagenicity</b>	: May cause heritable genetic damage. (Benzene) Mutagenicity studies on gasoline and gasoline blending streams have shown predominantly negative results.
<b>Carcinogenicity</b>	: Known human carcinogen. (Benzene) May cause leukaemia (AML - acute myelogenous leukemia). (Benzene) Inhalation exposure to mice causes liver tumours, which are not considered relevant to humans.
<b>Reproductive and Developmental Toxicity</b>	: Causes foetotoxicity at doses which are maternally toxic. (Toluene) Causes adverse effects on the foetus based on animal studies. (Toluene) Many case studies involving abuse during pregnancy indicate that toluene can cause birth defects, growth retardation and learning difficulties. (Toluene) Ethanol, a component of this material, may cause birth defects and/or miscarriages following high oral doses.
<b>Additional Information</b>	: Exposure to very high concentrations of similar materials has been associated with irregular heart rhythms and cardiac arrest. Prolonged and repeated exposures to high concentrations have resulted in hearing loss in rats. Solvent abuse and noise interaction in the work environment may cause hearing loss. (Toluene) Abuse of vapours has been associated with organ damage and death. (Toluene) Myelodysplastic syndrome (MDS) was observed in individuals exposed to very high levels (50 ppm to 300 ppm range) of benzene over a long period of time in the workplace. The relevance of these results to lower levels of exposure is not known. (Benzene)

**12. ECOLOGICAL INFORMATION**

Fuels are typically made from blending several refinery streams. Ecotoxicological studies have been carried out on a variety of hydrocarbon blends and streams but not those containing additives. Information given is based on a knowledge of the components and the ecotoxicology of similar products.

<b>Acute Toxicity</b>	: Toxic:LL/EL/IL50 1-10 mg/l(to aquatic organisms)(LL/EL50 expressed as the nominal amount of product required to
-----------------------	---

**Material Safety Data Sheet**

<b>Mobility</b>	: prepare aqueous test extract). Floats on water. Evaporates within a day from water or soil surfaces. Large volumes may penetrate soil and could contaminate groundwater. Contains volatile constituents.
<b>Persistence/degradability</b>	: Major constituents are expected to be inherently biodegradable. The volatile constituents will oxidize rapidly by photochemical reactions in air.
<b>Bioaccumulation</b>	: Contains constituents with the potential to bioaccumulate.
<b>Other Adverse Effects</b>	: Films formed on water may affect oxygen transfer and damage organisms.

**13. DISPOSAL CONSIDERATIONS**

<b>Material Disposal</b>	: Recover or recycle if possible. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations. Waste arising from a spillage or tank cleaning should be disposed of in accordance with prevailing regulations, preferably to a recognised collector or contractor. The competence of the collector or contractor should be established beforehand. Do not dispose into the environment, in drains or in water courses. Do not dispose of tank water bottoms by allowing them to drain into the ground. This will result in soil and groundwater contamination.
<b>Container Disposal</b>	: Drain container thoroughly. After draining, vent in a safe place away from sparks and fire. Residues may cause an explosion hazard. Do not, puncture, cut, or weld uncleaned drums. Send to drum recoverer or metal reclaimer. Do not pollute the soil, water or environment with the waste container.
<b>Local Legislation</b>	: Disposal should be in accordance with applicable regional, national, and local laws and regulations. Local regulations may be more stringent than regional or national requirements and must be complied with.

**14. TRANSPORT INFORMATION****ADG**

UN number	1203
Proper shipping name	GASOLINE
Class	3
Packing group	II
Hazchem Code	3YE

**IMDG**

Identification number	UN 1203
Proper shipping name	PETROL
Class / Division	3
Packing group	II
Marine pollutant:	Yes

## Material Safety Data Sheet

### IATA (Country variations may apply)

UN No. : 1203  
Proper shipping name : Gasoline  
Class / Division : 3  
Packing group : II

---

## 15. REGULATORY INFORMATION

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

**SUSDP Schedule** : Not scheduled. When packed in containers having capacity of greater than 20 litres.  
S5. When packed in containers having capacity of less than 20 litres.

**AICS** : All components are listed or exempt

**Classification triggering components** : Contains gasoline, low boiling point naphtha, unspecified.

**Other Information** : National Code of Practice for the Preparation of Material Safety Data Sheets [NOHSC:2011] List of Designated Hazardous Substances [NOHSC:10005]. Approved Criteria for Classifying Hazardous Substances [NOHSC:1008]. Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment [NOHSC:1003]. Australian Dangerous Goods Code. Standard Uniform Scheduling of Drugs and Poisons.

---

## 16. OTHER INFORMATION

**Additional Information** : This document contains important information to ensure the safe storage, handling and use of this product. The information in this document should be brought to the attention of the person in your organisation responsible for advising on safety matters.

## Material Safety Data Sheet

### R-phrase(s)

R11	Highly flammable.
R12	Extremely flammable.
R38	Irritating to skin.
R45	May cause cancer.
R46	May cause heritable genetic damage.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R63	Possible risk of harm to the unborn child.
R65	Harmful: May cause lung damage if swallowed.
R67	Vapours may cause drowsiness and dizziness.

<b>MSDS Version Number</b>	: 1.1
<b>MSDS Effective Date</b>	: 08.04.2010
<b>MSDS Revisions</b>	: A vertical bar ( ) in the left margin indicates an amendment from the previous version.
<b>MSDS Regulation</b>	:
<b>Uses and Restrictions</b>	: This product must not be used in applications other than those recommended in Section 1, without first seeking the advice of the supplier. This product is not to be used as a solvent or cleaning agent; for lighting or brightening fires; as a skin cleanser. This product is designed only to suit automotive applications and no provision is made for the requirements of aviation applications.
<b>MSDS Distribution</b>	: The information in this document should be made available to all who may handle the product.
<b>Disclaimer</b>	: This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.