



# SHELL DEODOURISED KEROSENE INDUSTRIAL AND DOMESTIC HEATING FUEL

## DESCRIPTION

Shell Deodourised Kerosene is a premium quality product for use in all kerosene burning applications including heating and refrigeration. It is suitable for space heaters with wick or sleeve type burners where it burns cleanly and uniformly with no objectionable odours or deposits. In lamps it gives a bright dependable light with no tendency to flicker. It is dyed to a light blue colour and has a deodorant added to mask the petroleum smell.

## HEALTH & SAFETY

Shell Deodourised Kerosene is a flammable liquid, classified as a Dangerous Goods Class 3 Packaging Group III for transportation purposes. Avoid contact with the skin and eyes, and breathing vapours or mists.

For further guidance on product health and safety refer to the appropriate Shell Material Safety Data Sheet.

## TYPICAL CHARACTERISTICS

DESCRIPTION	UNITS	METHODS	TYPICAL
Colour	-	Visual	Blue
Density @ 15 °C	kg/L	ASTM D1298	0.795
Flash Point	°C	IP 170	42
Distillation	°C	ASTM D86	
Initial Boiling Point			155
Final Boiling Point			234

### Document Information

PDS Number:	00791
Date Revised:	24 <sup>th</sup> January 2001